

KNOWLEDGE BASE · PUBLIC DOCUMENT

Running a Perl or CGI script on your hosting: permissions, line endings and the 500 that follows

cPanel & WHM

CODE

RLX-AO-KB-1854

VERSION

v2026.10.15

COUNTRY · LANGUAGE

Angola · English

Interweb Angola

RLX Angola, Lda. · Group RLX Holdings

Tax ID (NIF) 500 260 5724 · Commercial registration no. 26464-25/250724

<https://www.meu.interweb.ao/knowledgebase/1854>



The short answer: Perl and CGI scripts (many old forms and counters) work on hosting, but they are demanding: the file must have **execute permission (755)**, the first line must point to the **right Perl**, the lines must end as on Linux (**LF**), and the script must start by writing a **header**. Failing any one gives the same error: 500.

A minimal script that should work

Create a file called `test.cgi` with this content:

```
#!/usr/bin/perl  
print "Content-type: text/html\n\n";  
print "<h1>It works</h1>";
```

Upload it to the site's `cgi-bin` folder (or to the folder where CGI is enabled), give it permission **755** and open `your-domain.com/cgi-bin/test.cgi`. If “It works” appears, the rest is your script.

The causes of error 500, in order

Cause	How to recognise it	What to do
The header is missing	The log says “Premature end of script headers”.	The first thing the script writes must be <code>Content-type: text/html</code> followed by an empty line.
Wrong permission	The file has no execute permission, or is too open (777).	Set 755 on the script and the folder: File permissions .
Wrong Perl path	The first line (<code>#!/usr/bin/perl</code>) does not exist on this server.	Confirm Perl’s path on your server (in a terminal, <code>which perl</code>) or ask us.
Windows line endings (CRLF)	The script was written on Windows and uploaded as binary: the first line becomes <code>“/usr/bin/perl^M”</code> , which does not exist.	Save the file with Unix line endings (LF) in the editor, or upload it in text mode by FTP.
An error in the code itself	The log shows a line of the script.	Run it in a terminal: <code>perl -c test.cgi</code> checks the syntax.
A missing Perl module	“Can’t locate ... in @INC”.	See the modules in cPanel, or ask us to install it.

Old scripts are a risk. Many were never updated and have known flaws (forms that let anyone send e-mail, for example). Before using them, see whether there is a current alternative: **A safe, spam-free form**. To read the log, see **Reading the Errors pages**.

For everything that runs here, Perl included, see **Which technologies run here**. And for error 500 in general: **Error 500**.

Does the script still give 500? Open a ticket with the address, the file’s path and the log line.

[Open a support ticket](#)

SEE ALSO

[Which technologies run here: PHP, Node, Python, Perl, games and the limits](#)

[Error 500 Internal Server Error: finding the cause, step by step](#)

[File permissions explained: what 755, 644 and 777 mean](#)

[Reading the Errors and Raw Access pages in cPanel when a page fails](#)



Online version of this document

Interweb is a leading internet services company, with a mission to help businesses to be born and prosper through technology.

2020

FOUNDED

37,000+

CLIENTS

130+

SIGN-UPS A DAY

Interweb Angola

RLX Angola, Lda. • Group RLX Holdings

TAX ID (NIF)

500 260 5724

COMMERCIAL
REGISTRATION NO.

26464-25/250724

REGISTERED OFFICE

Rua Direita do Patriota, Bairro Dangereux
Belas, Luanda, Angola

CONTACT

info@interweb.ao • +244 942 011 191 • www.interweb.ao

OPENING HOURS

Monday to Friday - 08 AM to 04 PM
Saturday & Sunday - Closed