interweb

Generated on 28/11/2026 20:41

KNOWLEDGE BASE · PUBLIC DOCUMENT

Using your agent in n8n or another OpenAI-compatible app: agent/ as the model

Agents Through the API

CODE	VERSION	COUNTRY · LANGUAGE
RLX-AO-KB-3064	v2026.11.28	Angola · English

Interweb Angola
RLX Angola, Lda. · Group RLX Holdings
Tax ID (NIF) 500 260 5724 · Commercial registration no. 26464-25/250724

https://www.meu.interweb.ao/knowledgebase/3064

Using your agent in n8n or another OpenAI-compatible app: agent/ as the model

Agents Through the API Created on **November 28, 2026** 2 min read



An app that talks to OpenAI in the chat format also talks to your agents. It needs three things: our base address, your key and, in place of the model, `agent/` followed by the agent id.

The three fields

Field	What to enter
Base address (Base URL)	`https://api.interweb.ao/v1`
Key (API Key)	An **API Center** key with `ai:read` and `ai:write`
Model	`agent/` and the id, copied from Use through the API

Agents are used in the chat, `POST /v1/chat/completions`. If the app has an option to use another format, such as the Responses API, leave it off.

In n8n

1. Create the OpenAI credential with our address in Base URL, as in **using All in One AI in n8n**.
2. In the OpenAI Chat Model node, choose that credential. In the model field, switch from From List to ID and type `agent/...`.
3. Leave the Use Responses API option off.

You can also use the HTTP Request node, with `POST` to `https://api.interweb.ao/v1/chat/completions`, the key in Bearer Auth and this JSON body:

```
{
  "model": "agent/7c1e9a42-b35d8f06-a2c4e719-5d0b3f8e",
  "messages": [
    { "role": "user", "content": "Which services do you offer on Saturdays?" }
  ],
  "max_tokens": 400
}
```

Or **our n8n node**, with the AI operation Chat with a text model: in the model, type the agent id.

What the app can change

The model is always the agent's. The app's maximum tokens and temperature can lower the agent's, but never go above them. If the app has a system instructions field, leave it empty whenever you can: the agent's instructions and knowledge already go with every request, and extra text only spends tokens.

Testing

With a `sandbox_` key, the answer is always "Resposta de teste (sandbox).": it confirms the address, the key and the id without spending. If the app tests the credential with the model list, your agents show up there first, with the id `agent/...`.

A `404 model_not_found` means a wrong id or an agent from another account; a `409 agent_paused`, a paused agent. See **agent errors through the API**.

RECOMMENDED

Want your agent in your n8n workflows? See All in One AI.

See All in One AI →

SEE ALSO

- **Using All in One AI in n8n: the OpenAI credential with our address, or the HTTP Request node**
- **Any app that accepts an OpenAI-compatible address: the base URL, the key and the model id**
- **Our n8n node: domains, DNS, VPS, SMS, e-mail and AI in your workflows**
- **Agent errors through the API: agent_paused and model_not_found**
- **All in One AI**

interweb

Interweb Angola

RLX Angola, Lda. · Group RLX Holdings

TAX ID (NIF)	500 260 5724
COMMERCIAL REGISTRATION NO.	26464-25/250724
REGISTERED OFFICE	Rua Direita do Patriota, Bairro Dangereux Belas, Luanda, Angola
CONTACT	info@interweb.ao · +244 942 011 191 · www.interweb.ao
OPENING HOURS	Monday to Friday - 08 AM to 04 PM Saturday & Sunday - Closed

Online version of this document

RLX-AO-KB-3064 · v2026.11.28 · Generated on 28/11/2026 20:41