interweb

Generated on 15/11/2026 00:10

KNOWLEDGE BASE · PUBLIC DOCUMENT

Connecting to MySQL from PHP: mysqli and PDO, with a working example

Remote Access & Code

CODE	VERSION	COUNTRY · LANGUAGE
RLX-AO-KB-742	v2026.10.10	Angola · English

Interweb Angola
RLX Angola, Lda. · Group RLX Holdings
Tax ID (NIF) 500 260 5724 · Commercial registration no. 26464-25/250724

https://www.meu.interweb.ao/knowledgebase/742

Connecting to MySQL from PHP: mysqli and PDO, with a working example

Remote Access & Code Created on **October 10, 2026** 2 min read



PHP has two ways of talking to the database: **mysqli** (MySQL and MariaDB only) and **PDO** (which also serves PostgreSQL and others). For a new project PDO is the safe choice. With both, the host is `localhost`, and the database and user names carry the **account prefix**.

A complete example with PDO

1. Create the database, the user and the privileges in cPanel. See **creating a user and the privileges**.

2. Create a file `db-test.php` in the site folder with this content (swap the three values for yours):

```
<?php
$dsn = 'mysql:host=localhost;dbname=account_database;charset=utf8mb4';
try {
$pdo = new PDO($dsn, 'account_user', 'your-password-here', [PDO::ATTR_ERRMODE =>
PDO::ERRMODE_EXCEPTION]);
$row = $pdo->query('SELECT NOW() AS now_time')->fetch(PDO::FETCH_ASSOC);
echo 'Connected: ' . $row['now_time'];
} catch (PDOException $e) {
error_log($e->getMessage());
echo 'Connection failed.';
}
```

3. Open `db-test.php` in the browser. You should see *Connected* and the date. If you see *Connection failed*, the reason is in the PHP error log. See **where the error log is**.

4. **Delete the test file.** It has done its job.

The same connection with mysqli, and a safe query

With `mysqli` you connect using `new mysqli('localhost', 'account_user', 'password', 'account_database')` and, right after, `$link->set_charset('utf8mb4')`. With either library, **never glue variables into the SQL text**: use prepared statements, where the value travels separately.

Library	Prepared statement	Notes
PDO	`$st = $pdo->prepare('SELECT * FROM customers WHERE email = ?'); $st->execute([$email]);`	Works for MySQL, MariaDB and PostgreSQL. You change the DSN.
mysqli	`$st = $link->prepare('SELECT * FROM customers WHERE email = ?'); $st->bind_param('s', $email); $st->execute();`	MySQL and MariaDB only.

Three things that cause errors:
Using the database name *without* the prefix (MariaDB answers *Access denied*); forgetting to link the user to the database in cPanel; and writing the password into code and publishing it in a repository. Keep the details outside the code: see **passwords outside the code**.

Where to keep the connection details

In the example the values sit in the file itself, just for the test. In a real application, put them in a configuration file **outside** `public_html` (in the folder above, which the web server does not serve) and include it with `require`. That way, if PHP ever fails and shows the code instead of running it, the password does not leak. Note also `ERRMODE_EXCEPTION`: it turns an SQL error into an exception you can see, instead of a silence in which nothing happens. And open **one connection per request**, not one per query.

Accents coming out wrong?
The connection charset has to be `utf8mb4`, as in the example. See **the question marks in your text**.

NEED A HAND?

The example runs and your application still will not connect? Show us the exact error, without the password, and we will look.

Open a support ticket →

SEE ALSO

Connecting to your database from Python and Node.js →

Keeping passwords out of your PHP code: .env files and the right permissions →

Error establishing a database connection: the causes, in order →

interweb

Interweb Angola

RLX Angola, Lda. · Group RLX Holdings

TAX ID (NIF)	500 260 5724
COMMERCIAL REGISTRATION NO.	26464-25/250724
REGISTERED OFFICE	Rua Direita do Patriota, Bairro Dangereux Belas, Luanda, Angola
CONTACT	info@interweb.ao · +244 942 011 191 · www.interweb.ao
OPENING HOURS	Monday to Friday - 08 AM to 04 PM Saturday & Sunday - Closed

RLX-AO-KB-742 · v2026.10.10 · Generated on 15/11/2026 00:10

Online version of this document