interweb

Generated on 15/11/2026 00:12

KNOWLEDGE BASE · PUBLIC DOCUMENT

Updating n8n safely

n8n Setup & Hosting

CODE	VERSION	COUNTRY · LANGUAGE
RLX-AO-KB-910	v2026.10.10	Angola · English

Interweb Angola
RLX Angola, Lda. · Group RLX Holdings
Tax ID (NIF) 500 260 5724 · Commercial registration no. 26464-25/250724

https://www.meu.interweb.ao/knowledgebase/910

Updating n8n safely

n8n Setup & Hosting Created on **October 10, 2026** 3 min read



You update n8n by pulling the new image and recreating the container. Your data stays, because it lives in the volume. What can go wrong is not the command: it is **jumping versions without reading the notes** and **having no backup** to go back to. Do it in this order.

The update, in order

1. **Take a backup first.** Data, compose file and encryption key, as in **backing up n8n**. When it starts on a new version, n8n may change the structure of the data, and that does not undo itself.

2. **Read the release notes** on the project's site, especially if you are skipping several versions at once. That is where the changes that force you to alter workflows or variables are listed.

3. **Pin a version in the compose file**, instead of a tag that always moves forward. The exact tag names are on the official image page. That way you always know which version you are on and it changes only when you decide.

4. **Pull and recreate** with `docker compose pull` and `docker compose up -d`.

5. **Check the logs** with `docker compose logs`. Look for errors in the first moments.

6. **Test the important workflows** by hand, one by one: a webhook, a schedule, one credential of each kind.

What usually breaks

Symptom	Likely cause	What to do
n8n does not start afterwards	An old variable is no longer accepted, or the data migration failed.	Read the logs; compare your variables with the release notes.
A node stopped working	Its behaviour changed or it was replaced.	Look the node up in the documentation for your version.
Credentials throw errors	The encryption key changed, or was deleted along with the volume.	Put the original key back.
Webhooks do not answer	The new container lost `WEBHOOK_URL`.	Restore the variable. See **n8n webhooks**.

Going back is not always just changing the version.
If the new version already altered the structure of the data, returning to the old one may not work. The safe road is to restore the backup you took at the start and start the old version.

When to update

Update from time to time, without hurry, but do not let it drift too long. An installation left alone for a long time piles up known security flaws and makes the next jump riskier. Do it outside the hours when your important workflows run, and with time to test them. The general method for any application in Docker is in **updating a Docker application without losing data**.

If you have critical workflows
, rehearse the update on a copy: restore your backup on a second VPS or in a separate folder, update there, and only then do the real one. Also free up disk space: **Docker filling the disk**.

RECOMMENDED
Need another VPS to rehearse the update on?
See the VPS servers →

SEE ALSO

Backing up n8n →

- Updating a Docker application without losing data
- Docker filling the disk: images, volumes and logs

interweb

Interweb Angola

RLX Angola, Lda. · Group RLX Holdings

TAX ID (NIF)	500 260 5724
COMMERCIAL REGISTRATION NO.	26464-25/250724
REGISTERED OFFICE	Rua Direita do Patriota, Bairro Dangereux Belas, Luanda, Angola
CONTACT	info@interweb.ao · +244 942 011 191 · www.interweb.ao
OPENING HOURS	Monday to Friday - 08 AM to 04 PM Saturday & Sunday - Closed

Online version of this document

RLX-AO-KB-910 · v2026.10.10 · Generated on 15/11/2026 00:12